

Advanced Vacuum Steam Autoclave

SQ-Z60



Product features

- ★ 3-times pre-vacuum , effective discharge cold air from chamber to improve steam efficiency.
- ★ Internal steam generator , PLC control ,space and energy saving .
- ★ The post-sterilization hot steam is cooled down before discharge from machine
- ★ Equipped with water quality monitor . extend the machine service life .

Capacity	200 Liter
Power Supply	AC 380V , 50Hz
Working Pressures	210kPa-230kPa (0.21-0.23 MPa)
Safety Over-pressure	1.Over-pressure warning alarm 2. Safe pressure relief valve 3. Over-temperature shut-off device
Safety Door Interlock	PLC set: the door can't open while vessel is under pressure; can't start up if the door is not properly closed
Safety Emergency Shut-off	In a readily accessible location
Safety Surfaces	Surfaces NOT exceeding 50°C
Door	Mechanical rotating locking with electronic sensor
Indicator For Temperature	± 1% accuracy over the scale range 50°C to 150°C; 0.1°C resolution for digital display
Display indicators	Door locked, operation in progress, major operating cycle stages, and cycle complete ,times ,temperature , pressure ,fault condition readable by normal vision from a distance of 1.2 m
Manuals	English language. 1. Operation instructions (including process description), 2. Loading and maintenance procedures. 3. Short-form of operation and loading procedures.
Spare Parts(option)	a. Heating element b. Door seal/gasket c. Replacement air filter d. Safety valve e. Pressure and temperature gauges

Exclusive Distributor



PT. PERMANA PUTRA MANDIRI

MEDICAL EQUIPMENTS SUPPLIES AND SERVICES

Jl. Taman Mini Indonesia Indah (TMII)

Pintu II Atas No. 43 Cipayung, Jakarta Timur, Indonesia

Telp. : +62-21 841 5976, Fax : +62-21 840 7865

Email : info@ptppm.id, Website : www.ptppm.id