

DST-700G Electric Orthopedic Navigation Imaging Operation Table



- 1.DST-700G non-metal carbon fiber bed panel, non -metal carbon fiber head holder, low X-ray absorption high clear imaging results is the best choice used for 360°with the 3D and orthopedic navigation system.
- 2.Full carbon fiber head rest without metal, adopts Germany carbon fiber. The table top full carbon fiber material is China domestic patent technology R&D by ourselves, with high celar imaging results, low X-ray absorption.1150mm length of table top without metal, meet the requirements for 3D and 360°X-ray photograph of othopedics navigation systems.
- 3.Adopts the Germany DUKERON micro-motor, with electric gear mesh mechanism structure instead of the traditional hydraulic transmission. Germany beeline navigation rail, ensure the smooth movement.
- 4. Vertical/horizontal movement, head/foot, left/right tilt and adjustable back plate were controlled by different separated motors, they work individually and won't affect the others use.
- 5.One-reset function. Backup battery (80-100 operation time). Base use ABS industrial plastic, prevent glare impact and easy to clean, with two independent electric controlling system. High density memory mattress.
- 6.It is a China top high level operating table in same products, cooperated with Germany high level engineer design, full patent production on carbon fiber, ergonomic qualification match up C-arm using.
- 7. Optional installation for temperature control system.



Bed Panel Size(full carbon firber size)	(2400x 530) ± 10mm
Bed height from the ground (Without pads)	Min height: (700 ± 20) mm Max height: (1000 ± 20) mm
Lifting route (electric)	(300 ± 20) mm
Longitudinal route (electric)	(260 ± 20) mm
Head and foot tilt (electric)	Head down tilt: 25° ± 2 °
	Foot down tilt: 25 ° ± 2 °
Lateral tilt (electric)	Left: 21° ± 2 °
	Right: 21 ° ± 2 °
Back plate fold(electric)	Upwardt: 65 ° ± 2 °
	Downward: 20 ° ± 2 °
Leg plate fold (manual)	Upward: 35 ° ± 2 °
	Downward: 90 ° ± 2 °
Head section fold (manual)	Upward: 25 ° ± 2 °
	Downward: 90 ° ± 2 °
Table panel X-ray absorption coefficient	≤ 0.44mmAL
Power supply	220V 50Hz 300VA
Weight/capacity weight	330kg/ 450kg
Bed lock	Electric
Battery	One week (80-100 times)
CPR function	One reset function
	*

Standard Accessories








Y-003 lateral support







P-001/P-002 Y-004 lock block/clamping block carbon fiber arm support

Y-006 fixed belt







Y-009 leg support Y-008 anaesthesia screen D-001 orthopedic tractor



D-004 handing arm support



D-005 double deck arm support



D-006 extenor kinney bridge



knee crutches



D-002 cassette holder



D-008 adjustable spine pad



D-0010 upper limbs operation support



D-009 adjustable full carbon fibre spine shelf

Exclusive Distributor



PT. PERMANA PUTRA MANDIRI MEDICAL EQUIPMENTS SUPPLIES AND SERVICES JI. Taman Mini Indonesia Indah (TMII) Pintu II Atas No. 43 Cipayung, Jakarta Timur, Indonesia Telp.:+62-218415976, Fax:+62-218407865 Email: info@ptppm.id, Website: www.ptppm.id